

Boomlift / Manlift

Used Boom Lift Daly City - One of the commonest types of industrial equipment and aerial equipment is the boom lift. Commonly known as aerial work platforms, mobile elevating work platforms, cherry pickers, aerial devices and elevating work platforms, it was engineered to complete work at higher locations more efficient and easier. Many industries rely on boom lifts every day including retail locations, construction contractors, companies and warehouses. Staying safe while working at high altitude is essential for daily success. The material handling industry offers many boom lift models. Many models are capable of being operated by a single individual. Boom lifts are beloved in the agricultural and orchard industries, used to harvest fruit without requiring a separate ladder, they keep workers much safer since there is not climbing or bucket balancing involved. Since ladders require even, solid ground for setting them up safely, they can be unreliable in the agricultural industry. Relying on a boom lift is an easier and safer way to reach tree tops.

Gaining Access Over Obstacles Some boom lift models can move up and over obstacles, making them ideal for working over top of items safely and efficiently. This equipment is used in numerous industries including installing telephone poles and lines, maintaining overhead cables and window cleaning applications due to their ability to reach items when it is not practical to situate the machine directly underneath the issue. The articulated boom lift is an example that has numerous joints enabling it to bend over or under items. The articulated boom sections can move independently to grant operators access to many locations. Famous for their tight turning radius, articulated booms offer an ideal solution for narrow hallways and storage facilities. There are dual-fuel models that can work inside and outside; diesel is best utilized outside while interior locations rely on electric models.

Articulating Boom Lifts Articulated boom lifts are commonly found on construction sites and used in maintenance applications. They provide a vital piece to the fleet for servicing power lines and overhead wires. Certain models are outfitted with water cannons to be used in firefighting applications. Maximum reach can be attained with telescoping boom sections on certain models. There are articulating boom lifts complete with an additional jib that allows the platform to extend an extra 6 feet in any direction. These boom lifts go by the nickname of "spiders," since their legs can support the entire machine on steep or difficult terrain. Smaller units called interior articulating boom lifts are capable of fitting through doorways, making them valuable in retail, warehousing and storage facilities. Interior models are typically electric boom lifts due to their lack of dangerous carbon monoxide exhaust and quieter features.

Telescopic Boom Lifts Designed otherwise, telescopic boom lift models bend differently from articulating boom lifts. These models extend upwards and outwards, relying on hydraulics that extend and retract. The operator who is situated in the platform has the controls to operate and extend the lift on their own. Certain larger units feature a jib located at the top that looks similar to an articulating boom lift model. Boom lifts are available that reach higher than one-hundred and eighty feet. These machines are built to be stable and reliable. Some are able to extend to their full height capacity in less than 60 seconds. There are diesel and dual-fuel options with adjustable speed and weight range options from five hundred to one thousand pounds. Boom lifts can fit through tiny spaces and there are 4WD options on the market. In terms of combining height and reach, telescopic boom lifts are your best bet.

Jib The jib is the extension found at the end of the main boom and between the platform. Certain models offer an additional articulation point or hinge that allows the platform to travel horizontally and vertically. Jibs are an option on many telescoping and articulating boom lifts. Articulating models have a joint situated roughly halfway between the wheels and the platform to enable it to reach over an obstacle and then lower again if required.

Genie Articulating Boom Lifts The Genie Z-boom model is a common kind of articulating boom lift that can be found on the market. Designed to provide the most versatility in difficult to access spaces, this model has the capacity to lift up, over and out with superior positioning. In 1985, the first Genie Z-30/20 articulating Z-boom was introduced; their up-and-over capacity make them instantly popular and this design continues today. Proper Safety

Measures Of course, safety is the highest priority when operating any type of boom lift. Safety hazards must be advertised to everyone who is working in the area for best practices. Safely operating the equipment is a top priority for the operator and everyone in the working environment. Proper safety gear and communication need to be completed prior to operating. Ensure there are no flammable or combustible items, open flame or lit cigarettes near the machine, engine fuels or battery gases. It is important to have an accessible, securely mounted and visible fire extinguisher mounted within the operators' reach. It is important to maintain a clean work space around charging stations and work surfaces since clutter or tools could puncture tires or damage the machine or its components. Daily Maintenance Daily maintenance includes a visual inspection and consulting the maintenance manual to ensure the machine is up to date and will operate safely. These industrial machines rely on lifting and supportive mechanisms to stabilize the weight. Fasteners, straps and chains must be regularly checked to make sure they are safe working order. Single-use fasteners and components must not be reused as they may fail and become extremely dangerous. Discarded solvents and oils must be disposed of safely and in an approved container to prevent environmental contamination. Workbenches and workshop or garage areas need to have adequate lighting and ventilation. To organize and specify, maintenance is categorized into a variety of subsections including Annual Maintenance, Quarterly Maintenance, Programmed and Commissioning Maintenance Intervals. Maintenance Inspection Report Main aspects of the boom lift are categorized and divided to facilitate the inspection process. Common maintenance categories include Control and Function, Turntable, Booms, Platform, Drive Chassis and Engine. Improperly conducting maintenance can lead to unsafe working conditions, damaged components, reduced performance and ultimately downtime. A large part of keeping the boom lift secure and operational is the maintenance inspection report that ensures the operator is safe and monitors the machine's performance and service. Commissioning refers to a list of one-time maintenance procedures to be complete at 50 hours and at 150 hour intervals. There is quarterly and annual maintenance protocol that is conducted once or many times during the year. There are a variety of programmed maintenance procedures based on preparing the machine for pre-delivery machine operating. Consult your maintenance manual prior to operating to ensure all oil changes, battery life and fluid levels are primed for success.