

Very Narrow Aisle Forklift

Used Very Narrow Aisle Forklift Daly City - Warehousing solutions often focus on layout and space saving solutions in order to cut down on costly square footage and decrease travel time required to transport goods throughout the warehouse and loading dock areas. Very narrow aisle solutions allow for more space to be dedicated to the storage of goods because less space is required for aisle access. These warehouse configurations are often referred to as warehouse optimization. Warehouse Optimization Several benefits can be enjoyed for adding very narrow aisle warehouse optimization such as more storage space for the facility. Because very narrow forklift trucks were developed to take up less space in maneuvering, it is now possible to decrease warehouse aisle width to less than half the width required by standard forklifts. Numerous narrow aisle forklifts deliver better stacking heights to increase the storage capacity on a square foot basis. Costs can be drastically decreased with a narrow aisle forklift compared to a standard aisle configuration as less warehouse space is required for the same quantity of stock. Square footage is costly in urban areas and any way to reduce warehousing costs can save a company money. Adding a very narrow aisle width system can increase storage up to eighty percent when planned properly. In addition, a very narrow aisle layout allows for more rack faces as well as better access to products. Since greater quantities of products are situated in a more accessible area, there is less travel time needed for gathering and storing items. It is common for warehouses to use a very narrow or narrow aisle layout. Narrow aisles are usually those that use less than 11 feet of aisle width. Very narrow aisles reduce the aisle width further to around sixand-a-half feet. Both of these aisle widths provide significantly increased storage opportunities. Standard forklifts can have issues with turning in these aisle widths. To meet these challenges, several different types of very narrow forklifts have been specially developed for various types of tasks to allow easier maneuvering in narrow aisle widths. It is necessary to know the dimensions of the aisle when selecting a forklift for a certain job. Taking note of the proper dimensions will save valuable time and money by avoiding the mistake of acquiring a forklift that will not work in the intended application. Taking note of any utilities, columns or posts is necessary before choosing a particular narrow aisle forklift design to maximize warehouse optimization and safety. Very Narrow Aisle Forklift Trucks Rechargeable batteries are typical for powering very narrow aisle forklift trucks and most models are electric. These very narrow aisle trucks are more commonly available as stand-up riders, which helps increase productivity and operator comfort. The most popular kinds of very narrow aisle forklift trucks include turret or swing-mast, end-control riders, order pickers and reach trucks. Reach Forklift Trucks Reach trucks were designed as a version of the rider stacker forklift but specially modified for use in narrow aisles. It got its name by its function of reaching its forks forward to get to a load. The two kinds of reach trucks the moving carriage and the moving mast. The moving carriage works by raising and lowering the carriage, along with the operator. The moving mast raises and lowers the forks as the operator remains at ground level. The moving mast reach truck is generally considered the safer of the two types of reach trucks. Reach trucks utilize a pantograph system that is a jointed framework design enabling the driver to place and reach loads without moving the forklift. Order Pickers Order pickers have been designed and developed specifically for use in picking orders from high, typically hard-to-reach racks. Order pickers are specific for lighter stock items that can be lifted by hand. Order pickers elevate the operator to the level of goods to pick and identify particular items required for filling an order. End-Control Riders End-control riders are used to pick loads located at floor level and transport the load horizontally, rather than lift or lower loads from various heights. Turret or Swing-Mast Forklift The turret or swing mast very narrow aisle forklifts have a swivel mast that pivots and articulates. The mast swivels allowing pallets to be placed on either the left or right of the forklift. Guided Very Narrow Aisle Trucks Many very narrow aisle forklift trucks are able to be guided down aisles by wire or rail. Because the forklift is guided, thereby reducing the possibility of the forklift bumping racks while moving

down the aisle, the aisles can be extremely narrow. In rail-guided models, sets of rails are placed into the floor on each side of the aisle. They run the length of the aisle and also curve around the aisles' edge. The forklift is fitted with special wheel guides that slide into the rails, preventing the forklift from moving outside the rail guards. Running down the center of the aisle, wire-guidance forklifts rely on floor wires instead of rails. The wire-guides function similarly to the rail systems except the forklift has a wire-guide system to prevent the machine from traveling where it is not supposed to. Work Site Considerations Certain essential considerations need to be dealt with before using a narrow aisle configuration. The narrow aisle units feature tall racking systems. The floor construction and the racks need to be carefully taken into account for everyone's safety. There are four main locations that need to be ideally prepared before any racking system can be installed. These areas need to be monitored continuously including fixing cracks in the floor, ensuring the racks are straight, a level floor and an appropriate load capacity of the floor. Level Floor Due to the racking system height, any minor floor slope can gravely impact how plumb the racks are, particularly over time if loads are placed and removed repeatedly on the racks. The height of the racking system means that any minute floor slope can have a negative impact on how straight the racks are, especially over time when loads are continually removed and placed on the racks. Without this foundation of a level floor, the stability of the racks could be jeopardized. Crack Repair When cracks in the floor are spotted, they should be assessed and, when necessary, repaired immediately. Safety can become compromised when flooring cracks become 3/8 inches wide. They require proper filling with a substance that is as hard as the floor. Floor Load Capacity The floor should meet certain minimum requirements before considering a narrow aisle configuration. At a minimum, the floor should consist of 3,000 psi concrete as well as contain evenly distributed rebar approximately 3 to 4 inches below the surface. Depending on the configuration and load requirements, extra reinforcements may be necessary. Plumb Racks Installing the racks safely and correctly is vital for the entire system. There is a major chance of rack failure if improper installation occurs. Every rack needs to be plumb to ensure a safe system and work environment. Rack shims are recommended to make sure the racks are plumb within one inch at the thirty- foot rack height. If the above measures are not taken or are improperly implemented, it is likely to cause a racking failure. Employees can become hurt or killed in the event that racking failure occurs. Goods can be damaged along with forklifts and other equipment. Because of these reason, these measures are the most important part of implementing a narrow aisle configuration for warehousing optimization.